Revision Date: 2019-05-03

## 1. Product- and Company identification

#### **Product name:**

ANA Glass<sup>TM</sup> Varnish

## **Application of the product:**

Fixing of restauration materials Sealing of glass-ionomer-cements Sealing of dentin before applying inlays, crowns and bridges

## Details oft he supplier oft he safety data sheet:

Nordiska Dental AB

#### **Street:**

Framtidsgatan 1

#### **Zip-Code / Town**

SE-262 73 Ängelholm

#### **Contact for technical information**

+46 (0) 431 443360

#### Phone / Fax / E-Mail

+46 (0) 431 443360 / +46 (0) 431 443399 / info@nordiskadental.se

#### **Emergency information**

Phone: +46 (0) 431 443360

#### 2. Hazard identification

#### 2.1 Classification of the substance or mixture

According to Regulation (EC) No. 1272/2008:

- Eye Irrit. 2 causes serious eye irritation
- Flam. Liq. 2 liquid and vapor easily flammable

#### 2.2 Label elements

Labelling according to Regulation 1272/2008 (GHS/CLP)





Revision Date: 2019-05-03

H319	causes serious eye irritation
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection/
	hearing protection/
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
*****	
H225	liquid and vapor easily flammable
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources.No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting/] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges
P280	Wear protective gloves/protective clothing/eye protection/face protection/
	hearing protection/
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water [or shower)
P370+P378	In case of fire: Use to extinguish
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container to

## Additional hazard advices for human and environment:

EUHO66 Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

## 3. Composition/Information on ingredients

## **Chemical characterization:**

## **Hazardous ingredients:**

Ingredients	Cas-No.	Index-No.	EG-No.	Percentage (%)
Ethyl acetate	141-78-6	607-022-00-5	205-500-4	0 - 80
Nitrocellulose	9004-70-0	603-037-01-3		0 - 20
Ethanol	64-17-5	603-002-00-5	200-578-6	0-5

#### 4. First-Aid-Measures

#### **General advices**

Consult a doctor. Show the medicating doctor this material safety data sheet.

#### After inhalation

If breathed in, move person into fresh air. If not breathing give artificial respiration. Consult a doctor.

Revision Date: 2019-05-03

#### After skin contact

Wash off with plenty of soap and water. Consult a doctor.

#### After eye contact

Rinse thoroughly with plenty of water for at least 15 minutes with plenty of water and consult a doctor.

#### After swallowing

Do NOT induce vomitting. Never give anything by mouth to an unconscious person.

Rinse mouth with water. Consult a doctor.

## 5. Fire-Fighting-Measures

#### Suitable extinguishing agents

The fire is only erasable with water (cause of the nitrocellulose, that would still burn also without oxygen – contains Cellulose).

## Special protective equipment for fire-fighting

In case of fire, if necessary, use self-contained breathing apparatus.

#### **Further information**

Use water spray to cool unopened containers.

#### 6. Accidental release measures

## **Personal precautions**

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

## 7. Handling and storage

## Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition – No smoking.

Take measures to prevent the build up of electrostatic charge.

#### **Conditions for safe storage**

Keep container in a cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### 8. Exposure controls / Personal protection

## **Components with workplace control parameters**

Revision Date: 2019-05-03

Components	CAS-No.	Value	Control parameters	Update	Basis
Ethyl Acetate	141-78-6	AGW	400 ppm	2006-01-01	TRGS 900-
			1.500 mg/		workplace control
					parameters

Remarks: Senates commission for inspection of unhealthy working substances of DFG (MAK-Commission). A risk of « fruit damage » must not be suspected if workplace control parameters and the biological limit value (BGW) are observed.

#### **Personal protective equipment:**

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### **Hand protection**

The protection gloves has to correspond to the specifications of the EC-guideline 89/686/EWG and comply to the rule EN 374 which is due to it.

#### Eye protection

Face shield and safety glasses.

#### Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

#### **Hygiene measures**

The general preventive measures while working with chemicals are to be attended. Wash hands before breaks and at the end of workday.

PNCE and DNCL-Values as to be possibly worked out in a preparation safety report do not exist.

# 9. Physical and chemical properties

## **General information**

Form liquid Colour clear

Odour after Ethyl acetate

#### Safety data

Flash point <5°C

\*Ph no data available

\*Melting point ca. -84°C \*Ignition temperature ca. 427°C

\*Boiling point ca. 76,5 – 77,5°C \*Lower explosion limit ca. 2,2 % (V) \*Upper explosion limit ca. 11,5 %

Revision Date: 2019-05-03

\*Vapour pressure ca. 97,3 hPa at 20,0°C

\*Water solubility soluble

\*Partition coefficient log Pow: ca. 0,73

n-Octanol/water

\*This informations were adopted from the main component (Ethyl acetate).

## 10. Stability and reactivity

## **Chemical stability**

Stable under recommended storage conditions.

#### **Conditions to avoid**

Heat, flames and sparks.

#### Materials to avoid

Strong oxidizing agents

#### **Hazardous decomposition products**

Hazardous decomposition products formed under fire conditions. – Carbon oxides.

## 11. Toxicological information

#### **Acute toxicity:**

LD50 Oral - Rat - 5620 mg/kg

LC50 Inhalation – Mouse – 2 h – 45.000 mg/m3

LD50 Dermal – Rabbit - >180.000 mg/kg

#### Skin corrosion/irritation

No data available

## Serious eye damage/eye irritation

No data available

#### Respiratory or skin sensitization

No data available

#### Germ cell mutagenicity

No data available

## Carcinogenicity

This product is or contains a component that is not classifiable as to ist carcinogenicity based on ist IARC, ACGIH, NTP or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Revision Date: 2019-05-03

#### Reproductive toxicity

No data available.

# Specific target organ toxicity – single exposure (GHS)

May cause damage to organs.

## **Specific target organ toxicity – repeated exposure (GHS)**

No data available.

#### **Aspiration hazard**

No data available

#### **Potential health effects**

Inhalation: May be harmful if inhaled. Causes respiratory tract irritation.

Vapours may cause drowsiness and dizziness.

Ingestion: May be harmful if swallowed.

Skin: May be harmful if absorbed through skin. Causes skin irritation.

Repeated exposure may cause skin dryness or cracking.

Eyes: Causes eye irritation.

#### Signs and symptoms of exposure

Central nervous system depression, Drowsiness, narcosis, anemia

## **Additional information**

RTECS: AH5425000

#### 12. Ecological information

**Toxicity to fish:** LC50 – Oncorthynchus mykiss (rainbow trout)

350,00 - 600,00 mg/l - 96 h

LC50 – Pimephales promelas (fathead minnow)

220,00 - 250,00 mg/l - 96 h

**Toxicity to daphnia** EC50 – Daphnia magna (Water flea) and other aquatic 2.300,00 – 3.090,00 mg/l – 24h invertebrates: LC50 – Daphnia magna (Water flea)

560 mg/l - 46 h

**Toxicity to algae:** EC50 – No information available.

4.300,00 mg/l – 24 h EC50 – Selenastrum

1.800,00 - 3.200,00 mg/l - 72 h

#### Persistence and degradability

No data available

#### Mobility in soil

No data available

#### **Bioaccumulation potencial:**

Revision Date: 2019-05-03

No data available

#### Effect of the determination of the PTB- and vPvB-Report:

Endocrine disruption potential

If the material causes hormonal effects or prevents them is unknown to us.

#### Other adverse effects

No data available

## 13. Disposal considerations

#### **Product:**

#### **Recommendation:**

May not be disposed together with household garbage. Do not drain into canalisation.

To dispose of accordingly with notice of the local regulations of authority.

#### Disposal key

(see at disposal key for methacrylate-containing dental products) 16 03 05 organic waste, which contains hazard substances

## **Contaminated packaging:**

#### **Recommendation:**

Dispose of as unused product

# 14. Transport information

## **Landtransport ADR/RID:**



ADR/RID-GGVS/E class: 3 (F1) flammable liquid substances

Kemler-Number: 33 UN-Number: 1173 Packaging group: II Hazard Label: 3

Description of the good: 1173 ETHYL ACETATE

#### Maritime transport IMDG, GGVSea



IMDG/GGVSea-Class:3UN-Number:1173Label:3Packaging group:II

EMS-Number: F-E, S-D Marine pollutant: No

Correct technical name: ETHYL ACETATE

3

#### Air transport ICAO-TI and IATA-DGR



ICAO/IATA-Class:

Revision Date: 2019-05-03

UN/ID-Number: 1173 Label: 3 Packaging group: II

Correct technical name: ETHYL ACETATE

## 15. Regulatory information

#### 2.1 Classification of the substance or mixture

According to Regulation (EC) No. 1272/2008:

- Eye Irrit. 2 causes serious eye irritation
- Flam. Liq. 2 liquid and vapor easily flammable

## 2.2 Label elements

P303+P361+P353

## Labelling according to Regulation 1272/2008 (GHS/CLP)





H210	
H319	causes serious eye irritation
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
H225	liquid and vapor easily flammable
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources.No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting/] equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges
P280	Wear protective gloves/protective clothing/eye protection/face protection/

IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower)
P370+P378 In case of fire: Use ... to extinguish

hearing protection/...

Revision Date: 2019-05-03

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to...

#### Additional hazard advices for human and environment:

EUHO66 Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

#### Water hazard class:

WGK 1: slight water hazard (Estimation on the basis of the ingredients)

## \*16. Other information

#### Further applicable EG Guidelines

Guideline for preparation (1999/45/EC), at last changed by the guideline 2006/8/EC. Substance Guideline (67/548/EWG), at last changed by the guideline 2006/121 EC. REACH-Guideline (EC) No. 1907/2006

#### Manufacturer's suggested application restriction:

Only for commercial use – no public product

#### H-phrases on which is referred in chapter 2 and 3

Highly flammableIrritatin to eyes

EUHO66 Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

#### Changes compared to the last version

Adjustment to REACH

#### **Additional Information:**

Some of the information presented and conclusions drawn herein are from sources other than direct test-data on the product itself.

The contents and format of this MSDS are in accordance with EEC Commission (EC) No. 1907 / 2006.

## **Disclaimer of Liability**

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness.

The conditions or methods of handling, storage, use or disposal of the product are beyond

Revision Date: 2019-05-03

our control and may be beyond our knowledge.

For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.

This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.